COMMONWEALTH OF AUSTRALIA

PATENTS ACT 1952-1969

COMPLETE SPECIFICATION

(ORIGINAL)

23845/77

FOR OFFICE USE

Class Int. Class

Application Number: 23845-77

Lodged: 2 4 76 Accompanies Provisional Specification PC 5475.

Int Cl:- H61H -5/02.

A61H15/00C

Complete Specification—Lodged: 31 3 77

Accepted: LAPSED Sec 47(6)

Published: 5 10 78

Priority:

Related Art:

DOC

TO BE COMPLETED BY APPLICANT

Name of Applicant: Laszlo Szucs

A61H 23:00

A61H 201:06A

Address of Applicant: 1/27 Annandale Street Annandale, 2038

M/C

Cheque to value of $ 20.00

Actual Inventor: Laszlo Szucs

Address for Service: 1/27 Annandale Street Annandale, 2038

Complete Specification for the invention entitled: Electric Roller Massager

The following statement is a full description of this invention, including the best method of performing it known to me:—*

*Note: The description is to be typed in double spacing, pica type face, in an area not exceeding 9⅞" in depth and 6½" in width, on tough white paper of good quality and it is to be inserted inside this form.

16017/70 W. G. Murray, Government Printer, Canberra

TJ 29 3 79

This massager has been made for muscle pain, backacke lumbago and it helps prevent the first stages of paralyisis. It recouperates the muscles after a heavy day at work or sport, it even warms you up when you cold. There is a variable speed control for sensitive areas. The three rollers are made of soft rubber, in which the rollers A. and B. vibrate over the body as well as rock up and down, while roller C. is there to quide the machine over the body, and with an infrared radiator between the rollers which makes the treatment even more successfull.

Fig 1. ViewA. is the actual size and measurement of the massager.

Fig 1.

1. Main Frame
2. Electric motor 0.38 amps 240 volts or 12 volts D.C. on car battery
3. Motor Holder Clipses which is screwed on the frame
4. Puller wheel on the motor axis
5. Puller rubber ring is not showing on fig1.
6. Stander which holds the puller wheel scewed on the frame
7. Puller wheel
8. The axis for puller wheel
9. The ball bearing in the puller arm 5mm excenter of puller wheel
10. Ball bearings on both end of this puller wheel axis
11. The nuts on both end of the axis
12. Puller arm
13. Taflon bearingpressed in the arm of Rocking part
14. The axis scewed in puller arm
15. The rocker part
16. Teflon bearing pressed in alluminium tube No. 17
17. Alluminium tube
18. Soft rubber
19. Scew axis in the cintre of rocking arm
20. Teflon bearing pressed in the frame
21. The same as No. 20. on other side
22. Scew axis on the both end of the rocking part viewB. showing the scew axis, the rollers A.B.C. has the same on both ends and the rocking part 15. 20. having the same scew axis. The rocking part 15. can be attacked also in place of rollar C., but not neccary.

1/27 Annandale Street,
ANNANDALE N.S.W. 2038

29th March, 1977

Fig 2.

Showing the final appearence of the Electric Roller Massager with an off and on swich on handle and beside on top of the cover the knob which turns right or left, so controlling the speed.

Fig 3.

This simple S.C.R. circuit allows universal or AC/DC brush-type motors to be used over a wide range of speeds while still maintaining good torque. It can be placed in very small space anywhere on the main frame under cover.

LASZLO SZUCS

The claims defining the invention are as follows:*

This Massager has been made for muscle pain, backacke lumbago and it helps prevent the first stages of paralyisis. It recouperates the muscles after a heavy day at work or sport, it even warms you up when you cold. There is a variable speed control for sensitive areas. The three rollars are make of sofrubbe in which the rollars A. and B. vibrate over the body as well as rock up and down, while roller C. is there to guide the machine over the body, and with an infrared radiator between the rollers which makes the treatment even more successfull.

Fig 1. View A. is the Actual size and Measurement of the massage.

Dated this Tuesday day of 29th March, , 1977 LASZLO SZUCS

NAME OF APPLIC
(BLOCK LETTERS)

*Note: If there is insufficient space above to type the statement of claim, do not use this sheet, but use separate s of paper beginning with the words "The claims defining the invention are as follows:" and ending with the date an name of the applicant in block letters.

FIG. 1



MOTOR DRIVES OSCILLATIONS

FIG. 2



FIG. 3